



Computec AV LTD

Dell Ultrasharp 2000FP



General

Display Type	Flat panel display / TFT active matrix
Width	51.2 cm
Depth	22.7 cm
Height	50.8 cm
Weight	11.5 kg

Display

Diagonal Size	20.1"
Viewable Size	20.1"
Dot Pitch / Pixel Pitch	0.26 mm
Max Resolution	1600 x 1200 / 60 Hz
Colour support	24-bit (16.7 million colours)
Max Sync Rate (V x H)	76 Hz x 80 kHz
Controls / Adjustments	Brightness, contrast, H/V position, H/V size, sharpness, colour balance, saturation, input select, colour temperature, zoom, phase
OSD Languages	English, German, French, Spanish, Japanese
Display Screen Coating	Anti-glare, hard coating
Signal Input	DVI-D, VGA

Image

Image Colour Temperature	9300K, adjustable, 6500K
Image Brightness	240 cd/m ²
Image Contrast Ratio	350:1
Image Max H-View Angle	+80 / -80
Image Max V-View Angle	+80 / -80

Video Input

Analogue video Signal	RGB, S-Video, composite video
Digital Video Standard	Digital Visual Interface (DVI)

Expansion / Connectivity

Interfaces	1 x VGA - 15 pin HD D-Sub (HD-15) 1 x DVI-D - 24 pin digital DVI 1 x S-video input - 4 PIN mini-DIN 1 x composite video input - RCA
------------	--

Miscellaneous

Flat Panel Mount Interface	100 x 100 mm
Compliant Standards	Plug and Play

Power

Form Factor	External
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	60 Watt
Power Consumption Stand by / Sleep	5 Watt

Environmental Standards

EPA Energy Star Compliant	Yes
---------------------------	-----

Environmental Parameters

Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	10 - 80%
Max Altitude Operating	3 km