



Computec AV LTD

Sanyo PLC-XU48 Multimedia Projector



Technical specifications

General

Device Type	LCD projector
Width	29.8 cm
Depth	21.3 cm
Height	7.1 cm
Weight	2.7 kg

Projector / Panel

Image Brightness	3000 ANSI lumens
Image Contrast Ratio	450:1
Image Size	0.84 m - 7.62 m
Projection Distance	1.3 m - 10 m
Uniformity	85 %
Resolution	XGA (1024 x 768)
Native Aspect Ratio	4:3
Video Bandwidth	130 MHz
Display Format	786,432 pixels (1,024 x 768) x 3
Max Sync Rate (V x H)	100 Hz x 100 kHz
Bulb type	SHP 200 Watt
Bulb life cycle	1000 hour(s) / 2000 hour(s) (economic mode)

Computec AV Ltd, Unit 7 Dominion Business Park, Goodwin Road
Edmonton, London, N9 0BG Email: sales@computecgroup.com
Tel. +44 (0)20 8807 2002 Fax. +44 (0)20 8807 3818

Projector Lens System

Lens Aperture	F/1.7-2.5
Zoom Factor	1.2x
Keystone Correction Direction	Vertical
Vertical Keystone Correction	-20 / +20

Video Output

Analogue Video Format	NTSC, SECAM, PAL, PAL-N, PAL-M, NTSC 4.43
Analogue video Signal	RGB

Audio Output

Type	Speaker(s) - integrated
Sound Output Mode	Mono
Output Power / Channel	1 Watt

Expansion / Connectivity

Interfaces	1 x VGA input - 15 pin HD D-Sub (HD-15) 1 x audio line-in - mini-phone stereo 3.5 mm 1 x VGA input / output - 15 pin HD D-Sub (HD-15) 2 x audio line-out - mini-phone stereo 3.5 mm 1 x component video / audio input - RCA x 3 1 x S-video input - 4 PIN mini-DIN 1 x serial RS-232 - 8 PIN mini-DIN 1 x USB - 4 PIN USB Type B
------------	--

Power

Power Device	Power supply - internal
Voltage Required	AC 120/230 V
Power Consumption Operational	260 Watt

Manufacturer Warranty

Service & Support	3 years warranty
Service & Support Details	Limited warranty - 3 years Limited warranty - lamp - 1 year

Universal Product Identifiers

Part Number	PLC-XU48
-------------	----------